

HARTEX®

HARTEX® FIBERLOCK® 32 SPECIFICATIONS

SPECIFICATION DATA

Product Name	Hartex® FiberLock® 32
Material Weight	32 oz./sq. yd.
Density	8.5 lbs./cu. ft.
Thickness	0.313"
Product Dimensions	6' x 60' (40 SY)
Color	Gray
Tensile Strength	234.2 lbs
Traffic Class	Extra Heavy Duty
FHA Class	2
Material Content	100% Pre-Consumer Synthetic Fiber – Needle-punched and Thermal Bonded
Indoor Air Quality	CRI Green Label Plus-certified



FLAME CERTIFICATION

Pill Test	Pass	DOC-FF 1-70
Radiant Panel	Class I	ASTM E648
Smoke Test	<450	ASTM E662

THERMAL INSULATION

R-Value	2.10
---------	------

PRODUCT OVERVIEW

Hartex FiberLock carpet cushion is produced from a blend of 100% pre-consumer polypropylene and other synthetic fibers to create a premium-quality carpet cushion. FiberLock is designed for use in double-glue and stretch-in installations and offers a quick and easy installation process. It is recommended for high traffic-areas. FiberLock will not support the growth of mold or mildew. Contributes to LEED® credits. LEED points must be considered along with other building components and must be determined by the specifier/architect or LEED accredited representative.

Hartex FiberLock is designed for use in all commercial and hospitality areas, including, but not limited to: all public areas, meeting rooms, dorm rooms, offices, casinos, corridors, and retail space.



Leggett & Platt
INCORPORATED