

## dBarrier®

dBarrier® is a subfloor surface liner designed to be installed under sheet vinyl, LVT/LVP, WPC/SPC core, laminate, engineered wood, solid wood, or carpet tile with most backing systems. The product rolls out onto the subfloor, creating a sound and moisture barrier while also providing a "clean-start" liner between the subfloor and finished floor, leveling out any minor irregularities. It can be installed on, above, or below grade.



Clean-start  
Subfloor surface lining



Acoustical barrier  
Passive vibration isolation



Breathable moisture barrier  
with antimicrobial



Anti-fatigue comfort



No glue • single glue  
Double glue




Radiant heat-friendly

### APPLICATIONS

- Hospitality
- Multi-family
- Campus living
- Senior living
- Corporate
- Indoor public space

### PRODUCT SPECIFICATION DATA

Product code:	BV0340
Product name:	dBarrier®
Color:	Red clay
Material content:	100% synthetic rubber
Traffic classification:	Class III extra heavy
Material weight:	42 oz./sq. yd.
Density:	62 lbs./cu. ft.
Thickness:	1.42 mm (approx. 1/16")
Roll weight:	58 lbs.
Roll dimensions:	4' 6" x 44' 5" (22.2 sq. yds.) 200 sq. ft./roll



### COMFORT & DURABILITY (ASTM D3676, D3574)

Compression set @ 50%:	31.5%
Indentation force deflection @ 25%:	677.2 lbs. of force
Indentation force deflection @ 65%:	+5,000 lbs. of force

### GREEN CREDENTIALS (CRI Standards)

Recyclable:	100% recyclable
Indoor air quality:	CRI Green Label certified
VOC emissions:	Pass-Calif. section 01350

### FLAME CERTIFICATION (DOC-FF 1-70)

Pill test:	Pass
Smoke chamber:	Pass
Radiant panel:	Composite test w/ LVT, LVP, or carpet tile

### MOISTURE RESISTANCE (ASTM E96)

Resistance to topical liquid:	100%
Vapor permeance from slab:	Class III Vapor semi-permeable
Antimicrobial:	Guardian™

### ACOUSTICAL PERFORMANCE (ASTM E 90, E 492, E 2179)

Flooring installation	Flooring type	Thickness	Ceiling	Subfloor	IIC	Delta (ΔIIC)	STC
Floated	LVP	4.0 mm	Drop	8" slab	71	-	62
Floated	WPC core	8.0 mm	Drop	6" slab	69	26	61
Floated	Laminate	2.0 mm	Drop	6" slab	69	-	60
Floating/click	LVP	5.0 mm	Drop	6" slab	68	24	62
Double glue	LVP	2.0 mm	Drop	6" slab	68	21	60
Floating/click	LVP	4.0 mm	None	1.5" gypcrete	54	-	52
Floating/click	LVP	4.0 mm	Drop	.75" gypcrete	54	-	59