

HARTEX®

HARTEX® 28 SPECIFICATIONS

SPECIFICATION DATA

Product Name	Hartex® 28
Material Weight	28 oz./sq. yd.
Density	7.5 lbs./cu. ft.
Thickness	0.300"
Product Dimensions	6' x 60' (40 SY) 12' x 60' (80 SY)
Color	Gray
Tensile Strength	157.5 lbs
Traffic Class	Heavy
FHA Class	2
Material Content	100% Pre-Consumer Synthetic Fiber – Needle-punched and Thermal Bonded
Indoor Air Quality	CRI Green Label Plus-certified



FLAME CERTIFICATION

Pill Test	Pass	DOC-FF 1-70
Radiant Panel	Class I	ASTM E648
Smoke Test	<450	ASTM E662

THERMAL INSULATION

R-Value	2.01
---------	------

PRODUCT OVERVIEW

Hartex 28 is made from 100% pre-consumer synthetic fiber and will not support the growth of mold or mildew, and offers a quick and easy installation process. Hartex 28 has excellent thermal insulation and acoustical properties. Hartex 28 provides comfort underfoot and is less fatiguing than direct-glue-down installations. Contributes to LEED® credits. LEED points must be considered along with other building components and must be determined by the specifier/architect or LEED accredited representative.

Hartex 28 is designed for use in commercial and hospitality applications, including, but not limited to: guest rooms, meeting rooms, offices, dorm rooms, and retail space. Hartex 28 should be installed using conventional stretch-in installation only.



Leggett & Platt
INCORPORATED