

HARTEX®

HARTEX® 40 SPECIFICATIONS

SPECIFICATION DATA

| | |
|--------------------|--|
| Product Name | Hartex® 40 |
| Material Weight | 40 oz./sq. yd. |
| Density | 8.5 lbs./cu. ft. |
| Thickness | 0.390" |
| Product Dimensions | 6' x 60' (40 SY) 12' x 60' (80 SY) |
| Color | Gray |
| Tensile Strength | 261.4 lbs |
| Traffic Class | Extra Heavy |
| FHA Class | 2 |
| Material Content | 100% Pre-Consumer Synthetic Fiber – Needle-punched and Thermal Bonded |
| Indoor Air Quality | CRI Green Label Plus-certified |



FLAME CERTIFICATION

| | | |
|---------------|----------|-------------|
| Pill Test | Pass | DOC-FF 1-70 |
| Radiant Panel | Class II | ASTM E648 |
| Smoke Test | <450 | ASTM E662 |

THERMAL INSULATION

| | |
|---------|------|
| R-Value | 2.17 |
|---------|------|

PRODUCT OVERVIEW

Hartex 40 is made from 100% pre-consumer synthetic fiber and will not support the growth of mold or mildew, and offers a quick and easy installation process. Hartex 40 has excellent thermal insulation and acoustical properties. Hartex 40 provides comfort underfoot and is less fatiguing than direct-glue-down installations. Contributes to LEED® credits. LEED points must be considered along with other building components and must be determined by the specifier/architect or LEED accredited representative.

Hartex 40 is designed for use in commercial and hospitality applications, including, but not limited to: guest rooms, meeting rooms, offices, dorm rooms, and retail space. Hartex 40 should be installed using conventional stretch-in installation only.



Leggett & Platt
INCORPORATED