Tred-MOR[®] Floor Cushion and Acoustic Systems

GUEST ROOM Series for Stretch-in Carpet

Noise, Moisture, and Comfort Control



HORIZON 60[™]

Horizon 60[™] carpet cushion is a great choice for standard guest, residential, and dorm rooms, as well as private offices – providing long-lasting comfort to keep stretch-in broadloom carpets looking and feeling great. The textured design offers superior support and antimicrobial treatment helps to sustain a healthy environment.

RECOMMENDED HOTEL USAGE

| Economy | | Midscale | | Luxury | |
|---------|--|----------|--|--------|--|
| | | | | | |

APPLICATIONS

- Hotel Guest Room
- Campus Housing Dorm Room
- Senior Living Personal Quarters
- Business Office

FEATURES

- Made from high-performance synthetic rubber
- StainSTOP™ moisture barrier
- Guardian™ antimicrobial
- Lowest R-Values in the industry
- Exceeds CRI Green Label Plus for air quality

BENEFITS

- Provides insulation and noise suppression
- Offers superior support while improving carpet appearance and increasing carpet life
- Inhibits the growth of mold, mildew, and odorcausing bacteria
- Keeps spills from penetrating to subfloor
- Recommended as "Best Choice" by the Radiant Professionals Alliance
- 100% recyclable at the end of its useful life

PRODUCT SPECIFICATION DATA

| Product Code: | BV0134 |
|--------------------------------|--------------------------------|
| Product Name: | Horizon 60™ |
| Material Weight: | 60 oz./yd² |
| Density: | 18 lbs./ft ³ |
| Thickness: | 0.295" (5/16") |
| Product Dimensions: | 54″ x 40′ (20 yd²) |
| Approx. Shipping Wt.: | 80 lbs. per roll |
| Color: | Bright Green |
| Material Content: | Synthetic Rubber |
| Design Configuration: | Textured |
| Antimicrobial: | Guardian™ |
| Moisture Resistant: | 100% topical moisture |
| Indoor Air Quality: | CRI Green Label Plus Cert. |
| Flame Certification: | Pill Test – Pass (DOC-FF 1-70) |
| Thermal Insulation: | R-Value 0.40 |
| Impact Insulation Class (IIC): | 76 (6" concrete slab) |
| IIC Delta (ΔIIC): | No test data |
| Sound Transmission Class: | 50 (6" concrete slab) |
| | |