



## Silent Walk®

Silent Walk® is a subfloor surface liner designed to be installed under 6.5 mm + thickness LVT/LVP and WPC/SPC core; beneath any laminate, engineered, or solid hardwood floor; or carpet tile with any style backing. A 4.0 mil poly liner is shipped with each roll in the same size as the roll for optional use as a vapor barrier. The product rolls out onto the subfloor, creating a sound and moisture barrier while also becoming a "clean-start" liner between the subfloor and finished floor, leveling out any minor irregularities. It can be installed on, above, or below grade.



Clean-start  
Subfloor surface lining



Acoustical barrier  
Passive vibration isolation



Breathable moisture barrier  
with antimicrobial



Anti-fatigue comfort



No glue • single glue  
Double glue




Radiant heat-friendly

### APPLICATIONS

- Hospitality
- Casinos
- Campus living
- Corporate
- Senior living
- Multi-family
- Indoor public space
- Convention centers/ballrooms

### PRODUCT SPECIFICATION DATA

Product code:	BV0185
Product name:	Silent Walk®
Color:	Gray
Material content:	100% synthetic rubber
Traffic classification:	Class III extra heavy
Material weight:	62 oz./sq. yd.
Density:	31 lbs./cu. ft.
Thickness:	4.00 mm (5/32")
Roll weight:	79 lbs.
Roll dimensions:	4' 6" x 40' (20 sq. yd.) 180 sq. ft./roll



### ACOUSTICAL PERFORMANCE (ASTM E90, E492, E2179)

	6" Concrete Slab with Drop Ceiling	2' x 10' Wood Frame 3/4" Gypsum
Impact insulation class (IIC):	72	54
Delta IIC (ΔIIC):		N/A
Sound transmission class (STC):	65	57

### COMFORT & DURABILITY (ASTM D3676, D3574)

Compression set @ 50%:	35.2%
Indentation force deflection @ 25%:	264.9 lbs. of force
Indentation force deflection @ 65%:	1,964 lbs. of force

### GREEN CREDENTIALS (CRI Standards)

Recyclable:	100% recyclable
Indoor air quality:	CRI Green Label certified
VOC Emissions:	Pass-Calif. section 01350

### FLAME CERTIFICATION (DOC-FF 1-70)

Pill test:	Pass
Smoke chamber:	Pass
Radiant panel:	Composite test w/ LVT, LVP, or carpet tile

### MOISTURE RESISTANCE (ASTM E96)

Resistance to topical liquid:	100%
Vapor permeance from slab:	Class III Vapor semi-permeable Guardian™
Antimicrobial:	

### 4.0 MIL POLY (SHIPPED WITH PRODUCT)

Vapor permeance from slab:	Class I Vapor impermeable
----------------------------	------------------------------