

# ACOUSTIC UNDERLAYMENT FOR LAMINATE, SOLID, AND ENGINEERED HARDWOOD

## SILENT WALK™ SPECIFICATIONS

### SPECIFICATION DATA

Product Code:	BV0185
Product Name:	Silent Walk™
Material Weight:	62 oz./sq. yd.
Density:	31 lbs./cu. ft.
Thickness:	0.156"
Product Dimensions:	54" x 40' (20 sy.)
Color:	Grey
Material Content:	Made with Synthetic Rubber
Design Configuration:	Flat/Flat
Approx. Shipping Wt.:	79 lbs. per roll
Antimicrobial:	Guardian™
Moisture Resistant:	98%
StainSTOP™:	Yes
Indoor Air Quality:	CRI Green Label Plus-Certified



### ACOUSTICAL PERFORMANCE

IIC	IIC-72 w/floating laminate
STC	STC-65 w/floating laminate
RSD	Tested 4.5 dBA to 8.5 dBA quieter than standard foam paddings when tested as an assembly with laminate flooring. Measurements between 2000 Hz 4000 Hz utilizing ASTM E-492 tapping machine.

### FLAME CERTIFICATION

Pill Test:	Pass (DOC-FF 1-70)
------------	--------------------

### THERMAL INSULATION

R-Value:	0.27
----------	------

### PRODUCT FEATURES

Designed for use under floating hardwood and laminate. Silent Walk™ can be installed on, above, or below grade. Acoustically engineered to reduce sound transmission and impact noise in the room and the floor below. Can be installed with or without the 4 mil poly film included in every roll.



**SCI**  
**Sponge Cushion, Inc.**  
A Leggett & Platt COMPANY  
INCORPORATED