




Dubl-Stik® 1562

Tred-MOR® Dubl-Stik® commercial carpet cushion products have been the industry standard since 1985. They're engineered for high-traffic public spaces to keep carpets looking and feeling better, longer. Dubl-Stik® 1562 adds tensile strength and resiliency while also dramatically reducing the loss of carpet pile height. Recommended for extra-heavy commercial and public spaces, including institutional areas subject to CONTINUOUS rolling-wheel traffic.


 Anti-fatigue comfort

 Acoustical barrier
Passive vibration isolation

Available with

 Double glue or
Conventional stretch-in

 VaporFLO™ moisture barrier
with antimicrobial



APPLICATIONS

- Hospitality
- Casino
- Campus living
- Corporate
- Senior living
- Multi-family
- Indoor public space
- Convention centers/ballrooms

PRODUCT SPECIFICATION DATA

Product code:	BV0171
Product name:	Dubl-Stik™ 1562
Color:	Black
Material content:	100% synthetic rubber
Backing top:	Poly-tek
Backing bottom:	Spunbonded
Material weight:	62 oz./sq. yd.
Density:	33 lbs./cu. ft.
Thickness:	4.0 mm (.156" or 5/32")
Roll weight:	124 lbs.
Traffic classification:	Class III extra heavy
Roll dimensions:	4' 6" x 60' (30 sq. yds.) 270 sq. ft./roll

COMFORT & DURABILITY (ASTM D3676, D2646)

Compression set @ 50%:	6.4%
Compression load deflection @ 25%:	5.8 psi
Compression load deflection @ 65%:	39.1 psi
Breaking strength – length:	45.0 psi
Breaking strength – width:	41.0 psi

ACOUSTICAL PERFORMANCE (ASTM E90, E492, E2179)

	6" concrete bare slab	2' x 10" wood frame 3/4" gypsum
Impact insulation class (IIC):	65	55
Delta IIC (ΔIIC):	32	N/A
Sound transmission class (STC):	52	55

GREEN CREDENTIALS (CRI Standards)

Recyclable:	100% recyclable
Indoor air quality:	CRI Green Label certified
VOC emissions:	Pass Calif. section 01350

FLAME CERTIFICATION (DOC-FF 1-70, ASTM E662-06, E648)

Pill test:	Pass
Smoke density:	Pass
Radiant panel:	Composite test required w/ broadloom carpet or carpet tile and adhesive

MOISTURE RESISTANCE (ASTM E96)

Resistance to topical liquid:	100%
Vapor permeance from slab:	Class III
Antimicrobial:	Vapor semi-permeable Guardian™

