



Dubl-Stik[®] 2500

Tred-MOR[®] Dubl-Stik[®] 2500 carpet cushion features superior sound suppression, antimicrobial protection, and added tensile strength to keep commercial carpets clean, healthy, and comfortable. The unique design and resilient construction extend carpet life by providing superior support. Recommended for extra-heavy commercial and public spaces, including institutional areas subject to CONTINUOUS rolling-wheel traffic.



Anti-fatigue comfort



Acoustical barrier
Passive vibration isolation


Available with



Double glue or
Conventional stretch-in



VaporFLO[™] moisture barrier
with antimicrobial



APPLICATIONS

- Hospitality
- Casino
- Campus living
- Corporate
- Senior living
- Multi-family
- Indoor public space
- Convention centers/ballrooms

PRODUCT SPECIFICATION DATA

Product code:	BV0167
Product name:	Dubl-Stik [™] 2500
Color:	Black
Material content:	100% synthetic rubber
Backing top:	Poly-tek
Backing bottom:	Spunbonded
Material weight:	100 oz./sq. yd.
Density:	33 lbs./cu. ft.
Thickness:	6.35 mm (.250"/1/4")
Roll weight:	95 lbs.
Traffic classification:	Class III extra heavy
Roll dimensions:	4' 6" x 30' (15 sq. yds.) 135 sq. ft./roll

COMFORT & DURABILITY (ASTM D3676, D2646)

Compression set @ 50%:	15%
Compression load deflection @ 25%:	7.0 psi
Compression load deflection @ 65%:	45.0 psi
Breaking strength – length:	30.0 psi
Breaking strength – width:	25.0 psi

ACOUSTICAL PERFORMANCE (ASTM E90, E492, E2179)

	6" concrete bare slab
Impact insulation class (IIC):	77
Delta IIC (ΔIIC):	41
Sound transmission class (STC):	52

GREEN CREDENTIALS (CRI Standards)

Recyclable:	100% recyclable
Indoor air quality:	CRI Green Label certified
VOC emissions:	Pass Calif. section 01350

FLAME CERTIFICATION (DOC-FF 1-70, ASTM E662-06, E648)

Pill test:	Pass
Smoke density:	Pass
Radiant panel:	Composite test required w/ broadloom carpet or carpet tile and adhesive

MOISTURE RESISTANCE (ASTM E96)

Resistance to topical liquid:	100%
Vapor permeance from slab:	Class III
Antimicrobial:	Vapor semi-permeable Guardian [™]

