



Dubl-Stik® 2568 QL

With a long-standing history of providing comfort and support, Tred-MOR® Dubl-Stik® 2568 QL is engineered to keep high-traffic areas feeling better, longer. The added tensile strength provides a reduction in the loss of pile height in carpets. Future removal is also made significantly easier with the Quick-Lift backing system, allowing the carpet and cushion to release from the substrate without scraping. Recommended for heavy commercial and public spaces, including institutional areas subject to PERIODIC rolling-wheel traffic.



APPLICATIONS

- Hospitality
- Casino
- Campus living
- Corporate
- Senior living
- Multi-family
- Indoor public space
- Convention centers/ballrooms

PRODUCT SPECIFICATION DATA

Product code:	BV0176
Product name:	Dubl-Stik™ 2568 QL
Color:	Black
Material content:	100% synthetic rubber
Backing top:	Poly-Tek
Backing bottom:	Quick-Lift poly felt
Material weight:	68 oz./sq. yd.
Density:	22 lbs./cu. ft.
Thickness:	6.35 mm (.250"/1/4")
Roll weight:	138 lbs.
Traffic classification:	Class III extra heavy
Roll dimensions:	4' 6" x 60' (30 sq. yds.) 270 sq. ft./roll

COMFORT & DURABILITY (ASTM D3676, D2646)

Compression set @ 50%:	17.5%
Compression load deflection @ 25%:	3.1 psi
Compression load deflection @ 65%:	20.0 psi
Breaking strength – length:	45.0 psi
Breaking strength – width:	41.0 psi

ACOUSTICAL PERFORMANCE (ASTM E90, E492, E2179)

	6" concrete bare slab
Impact insulation class (IIC):	79
Delta IIC (ΔIIC):	43
Sound transmission class (STC):	53

GREEN CREDENTIALS (CRI Standards)

Recyclable:	100% recyclable
Indoor air quality:	CRI Green Label certified
VOC emissions:	Pass Calif. section 01350

FLAME CERTIFICATION (DOC-FF 1-70, ASTM E662-06, E648)

Pill test:	Pass
Smoke density:	Pass
Radiant panel:	Composite test required w/ broadloom carpet or carpet tile and adhesive

MOISTURE RESISTANCE (ASTM E96)

Resistance to topical liquid:	100%
Vapor permeance from slab:	Class III
Antimicrobial:	Vapor semi-permeable Guardian™

