






Dubl-Stik® 2580 QL

Dubl-Stik® 2580 QL carpet cushion has been the premium choice for hospitality and commercial public areas since 1985. With a tensile strength that's perfect for heavy foot and wheeled traffic, these cushions provide the ultimate support while reducing pile-height loss. Future removal is also made significantly easier with the Quick-Lift backing system, allowing the carpet and cushion to release from the substrate without scraping. Recommended for extra-heavy commercial and public spaces, including institutional areas subject to FREQUENT rolling-wheel traffic.

- | | | |
|--|---|---|
|  Anti-fatigue comfort |  Acoustical barrier Passive vibration isolation |  Easy removal Quick-lift technology |
|  Double glue or Conventional stretch-in |  VaporFLO™ moisture barrier with antimicrobial | |

APPLICATIONS

- Hospitality
- Casino
- Campus living
- Corporate
- Senior living
- Multi-family
- Indoor public space
- Convention centers/ballrooms

PRODUCT SPECIFICATION DATA

| | |
|-------------------------|---|
| Product code: | BV0182 |
| Product name: | Dubl-Stik™ 2580 QL |
| Color: | Black |
| Material content: | 100% synthetic rubber |
| Backing top: | Poly-Tek |
| Backing bottom: | Quick-Lift poly felt |
| Material weight: | 80 oz./sq. yd. |
| Density: | 26 lbs./cu. ft. |
| Thickness: | 6.35 mm (.250"/1/4") |
| Roll weight: | 155 lbs. |
| Traffic classification: | Class III extra heavy |
| Roll dimensions: | 4' 6" x 60' (30 sq. yds.) 270 sq. ft./roll |

COMFORT & DURABILITY (ASTM D3676, D2646)

| | |
|------------------------------------|----------|
| Compression set @ 50%: | 15.0% |
| Compression load deflection @ 25%: | 5.0 psi |
| Compression load deflection @ 65%: | 25.0 psi |
| Breaking strength – length: | 45.0 psi |
| Breaking strength – width: | 41.0 psi |

ACOUSTICAL PERFORMANCE (ASTM E90, E492, E2179)

| | |
|---------------------------------|-----------------------|
| | 6" concrete bare slab |
| Impact insulation class (IIC): | 78 |
| Delta IIC (ΔIIC): | 42 |
| Sound transmission class (STC): | 53 |

GREEN CREDENTIALS (CRI Standards)

| | |
|---------------------|---------------------------|
| Recyclable: | 100% recyclable |
| Indoor air quality: | CRI Green Label certified |
| VOC emissions: | Pass Calif. section 01350 |

FLAME CERTIFICATION (DOC-FF 1-70, ASTM E662-06, E648)

| | |
|----------------|---|
| Pill test: | Pass |
| Smoke density: | Pass |
| Radiant panel: | Composite test required w/ broadloom carpet or carpet tile and adhesive |

MOISTURE RESISTANCE (ASTM E96)

| | |
|-------------------------------|--------------------------------|
| Resistance to topical liquid: | 100% |
| Vapor permeance from slab: | Class III |
| Antimicrobial: | Vapor semi-permeable Guardian™ |

