




## Dubl-Stik<sup>®</sup> 2580

Tred-MOR<sup>®</sup> Dubl-Stik<sup>®</sup> 2580 carpet cushion products have been the premium choice for hospitality and commercial public areas since 1985. With a tensile strength that's perfect for heavy foot and wheeled traffic, these cushions provide the ultimate support – reducing pile-height loss and maintaining a comfortable look and feel. Recommended for extra-heavy commercial and public spaces, including institutional areas subject to FREQUENT rolling-wheel traffic.


 Anti-fatigue comfort

 Acoustical barrier  
Passive vibration isolation

Available with

 Double glue or  
Conventional stretch-in

 VaporFLO<sup>™</sup> moisture barrier  
with antimicrobial



### APPLICATIONS

- Hospitality
- Casino
- Campus living
- Corporate
- Senior living
- Multi-family
- Indoor public space
- Convention centers/ballrooms

### PRODUCT SPECIFICATION DATA

Product code:	BV0180
Product name:	Dubl-Stik <sup>®</sup> 2580
Color:	Black
Material content:	100% synthetic rubber
Backing top:	Poly-Tek
Backing bottom:	Spunbonded
Material weight:	80 oz./sq. yd.
Density:	26 lbs./cu. ft.
Thickness:	6.35 mm (.250"/1/4")
Roll weight:	155 lbs.
Traffic classification:	Class III extra heavy
Roll dimensions:	4' 6" x 60' (30 sq. yds.) 270 sq. ft./roll

### COMFORT & DURABILITY (ASTM D3676, D2646)

Compression set @ 50%:	15.0%
Compression load deflection @ 25%:	5.0 psi
Compression load deflection @ 65%:	25.0 psi
Breaking strength – length:	45.0 psi
Breaking strength – width:	41.0 psi

### ACOUSTICAL PERFORMANCE (ASTM E90, E492, E2179)

	6" concrete bare slab
Impact insulation class (IIC):	78
Delta IIC (ΔIIC):	42
Sound transmission class (STC):	53

### GREEN CREDENTIALS (CRI Standards)

Recyclable:	100% recyclable
Indoor air quality:	CRI Green Label certified
VOC emissions:	Pass Calif. section 01350

### FLAME CERTIFICATION (DOC-FF 1-70, ASTM E662-06, E648)

Pill test:	Pass
Smoke density:	Pass
Radiant panel:	Composite test required w/ broadloom carpet or carpet tile and adhesive

### MOISTURE RESISTANCE (ASTM E96)

Resistance to topical liquid:	100%
Vapor permeance from slab:	Class III
Antimicrobial:	Vapor semi-permeable Guardian <sup>™</sup>

