Tred-MOR[®] LEGACY Series



Dubl-Stik® 2580

Tred-MOR® Dubl-Stik® 2580 carpet cushion products have been the premium choice for hospitality and commercial public areas since 1985. With a tensile strength that's perfect for heavy foot and wheeled traffic, these cushions provide the ultimate support – reducing pile-height loss and maintaining a comfortable look and feel. Recommended for extra-heavy commercial and public spaces, including institutional areas subject to FREQUENT rolling-wheel traffic.



Anti-fatigue comfort



Acoustical barrier
Passive vibration isolation



Quik-LIFT® System



Double glue or Conventional stretch-in



VaporFLO[™] moisture barrier with antimicrobial

APPLICATIONS

Hospitality Senior living Casino Multi-family

Campus living
 Indoor public space

Corporate
 Convention centers/ballrooms

PRODUCT SPECIFICATION DATA

Product code: BV0180

Product name: Dubl-Stik™ 2580

Color: Black

Material content: 100% synthetic rubber

Backing top: Poly-Tek
Backing bottom: Spunbonded
Material weight: 80 oz./sq. yd.
Density: 26 lbs./cu. ft.

Thickness: 6.35 mm (.250"/1/4")

Roll weight: 155 lbs.

Traffic classification: Class III extra heavy Roll dimensions: 4' 6" x 60' (30 sq. yds.)

270 sq. ft./roll

COMFORT & DURABILITY (ASTM D3676, D2646)

Compression set @ 50%: 15.0%
Compression load deflection @ 25%: 5.0 psi
Compression load deflection @ 65%: 25.0 psi
Breaking strength – length: 45.0 psi
Breaking strength – width: 41.0 psi

ACOUSTICAL PERFORMANCE (ASTM E90, E492, E2179)

6" concrete bare slab

Impact insulation class (IIC): 78

Delta IIC (ΔIIC): 42

Sound transmission class (STC): 53

GREEN CREDENTIALS (CRI Standards)

Recyclable: 100% recyclable Indoor air quality: CRI Green Label

certified

VOC emissions: Pass Calif. section 01350

FLAME CERTIFICATION (DOC-FF 1-70, ASTM E662-06, E648)

Pill test: Pass Smoke density: Pass

Radiant panel: Composite test required

w/ broadloom carpet or carpet tile and adhesive

MOISTURE RESISTANCE (ASTM E96)

Resistance to topical liquid: 100% Vapor permeance from slab: Class III

Vapor semi-permeable

Antimicrobial: Guardian™













