



## Dubl-Stik® 3700

Since 1985, customers have relied on Tred-MOR® Dubl-Stik® 3700 carpet cushion to keep carpets looking and feeling better, longer. It's engineered to provide superior impact noise reduction and the support necessary to drastically reduce pile-height loss in carpets – all while offering premium comfort underfoot. Recommended for LIGHT COMMERCIAL suitable for luxury guest rooms, suites, and professional offices.



Anti-fatigue comfort



Acoustical barrier  
Passive vibration isolation



Double glue or  
Conventional stretch-in



VaporFLO™ moisture barrier  
with antimicrobial

### APPLICATIONS

- Hospitality guest room
- Senior living quarters
- Campus living quarters
- Business office

### PRODUCT SPECIFICATION DATA

Product code:	BV0157
Product name:	Dubl-Stik® 3700
Color:	Black
Material content:	100% synthetic rubber
Backing top:	Poly-Tek
Backing bottom:	Spunbonded
Material weight:	100 oz./sq. yd.
Density:	22 lbs./cu. ft.
Thickness:	9.40 mm (.370" or 3/8")
Roll weight:	102 lbs.
Traffic classification:	Class II light commercial
Roll dimensions:	4' 6" x 30' (15 sq. yds.) 135 sq. ft./roll

### COMFORT & DURABILITY (ASTM D3676, D2646)

Compression set @ 50%:	17.5%
Compression load deflection @ 25%:	3.0 psi
Compression load deflection @ 65%:	28.0 psi
Breaking strength – length:	45.0 psi
Breaking strength – width:	41.0 psi

### ACOUSTICAL PERFORMANCE (ASTM E90, E492, E2179)

	6" concrete bare slab
Impact insulation class (IIC):	83
Delta IIC (ΔIIC):	N/A
Sound transmission class (STC):	53

### GREEN CREDENTIALS (CRI Standards)

Recyclable:	100% recyclable
Indoor air quality:	CRI Green Label certified
VOC emissions:	Pass Calif. section 01350

### FLAME CERTIFICATION (DOC-FF 1-70, ASTM E662-06, E648)

Pill test:	Pass
Smoke density:	Pass
Radiant panel:	Composite test required w/ broadloom carpet or carpet tile and adhesive

### MOISTURE RESISTANCE (ASTM E96)

Resistance to topical liquid:	100%
Vapor permeance from slab:	Class III
Antimicrobial:	Vapor semi-permeable Guardian™

