Tred-MOR[®] LEGACY Series



Dubl-Stik® 3700

Since 1985, customers have relied on Tred-MOR® Dubl-Stik® 3700 carpet cushion to keep carpets looking and feeling better, longer. It's engineered to provide superior impact noise reduction and the support necessary to drastically reduce pile-height loss in carpets – all while offering premium comfort underfoot. Recommended for LIGHT COMMERCIAL suitable for luxury guest rooms, suites, and professional offices.



Anti-fatigue comfort



Acoustical barrier
Passive vibration isolation



Double glue or Conventional stretch-in



VaporFLO™ moisture barrier with antimicrobial

APPLICATIONS

- Hospitality guest room
- · Campus living quarters
- Senior living quarters
- Business office

PRODUCT SPECIFICATION DATA

Product code: BV0157

Product name: Dubl-Stik™ 3700

Color: Black

Material content: 100% synthetic rubber

Backing top: Poly-Tek
Backing bottom: Spunbonded
Material weight: 100 oz./sq. yd.
Density: 22 lbs./cu. ft.

Thickness: 9.40 mm (.370" or 3/8")

Roll weight: 102 lbs.

Traffic classification: Class II light commercial Roll dimensions: $4' 6'' \times 30'$ (15 sq. yds.)

135 sq. ft./roll

COMFORT & DURABILITY (ASTM D3676, D2646)

Compression set @ 50%: 17.5%
Compression load deflection @ 25%: 3.0 psi
Compression load deflection @ 65%: 28.0 psi
Breaking strength – length: 45.0 psi
Breaking strength – width: 41.0 psi

ACOUSTICAL PERFORMANCE (ASTM E90, E492, E2179)

6" concrete bare slab 83

Impact insulation class (IIC): 83

Delta IIC (Δ IIC): N/A

Sound transmission class (STC): 53

GREEN CREDENTIALS (CRI Standards)

Recyclable: 100% recyclable Indoor air quality: CRI Green Label

certified

VOC emissions: Pass Calif. section 01350

FLAME CERTIFICATION (DOC-FF 1-70, ASTM E662-06, E648)

Pill test: Pass Smoke density: Pass

Radiant panel: Composite test required

w/ broadloom carpet or carpet tile and adhesive

MOISTURE RESISTANCE (ASTM E96)

Resistance to topical liquid: 100% Vapor permeance from slab: Class III

Vapor semi-permeable

Antimicrobial: Guardian™













